

## EnOcean Easyclick thermostat receiver, flush mounting

Product Data Sheet



Mounting method	Flush mounted (plaster)
Degree of protection (IP)	IP20
Valve protection function	No
Manual switch	No
Number of binary inputs	1
Max. switching current (resistive load)	10Ampere
Number of outputs	1
Switching voltage	230-230Volt

**EnOcean Easyclick thermostat receiver,  
flush mounting**

Easyclick thermostat receiver for flush mounting, living space function for regulating heating temperature ON/ OFF: The receiver compares the room temperature transmitted by the room temperature sensor with the entered setpoint. A smaller value switches the relay ON, a higher value OFF (thermostat function). The relay output can be used directly to actuate 230 Vac thermal two-point valves. The energy lock function can be used for up to 10 programmed window contacts. When the window is closed, the receiver switches the actuator to OFF.

**Technical data:**

Supply voltage: 230 Vac, 50 Hz

Switching output: changeover contact, max 2500 W

Screw type terminals: max 1.5 mm<sup>2</sup>

Rating: IP 20 according to EN 60529

Installation: in flush mounting socket with blank cover and cable outlet

Housing height: 28 mm

Material No.	Article No.	EAN-code
00312296	D 451 FU-E RTR O.T.	4010105312294

---

**PEHA Elektro GmbH & Co.KG**

a Honeywell Company

Daimlerstraße 4

58553 HALVER

DEUTSCHLAND

Tel.: 02353 9118 001

Fax: 02353 9118 311

mail: [peha@honeywell.de](mailto:peha@honeywell.de)[www.peha.de](http://www.peha.de)

Änderungen vorbehalten. © Honeywell PEHA