

## EnOcean Easyclickpro baldachin receiver 1-channel

Product Data Sheet



Current supply	230 V AC
Mounting method	Flush mounted (plaster)
Colour	White
Suitable for degree of protection (IP)	IP20
Suitable for venetian-/roller shutter switch	No
Push button mode	Yes
Switching mode	Yes
With radio controlled push button	No
Number of relays	1
Halogen free	Yes
Radio frequency	868Megahertz
2 channel	no
bi-directional	yes
energy metering	no
potential-free contact	no

## EnOcean Easyclickpro baldachin receiver 1-channel

The bidirectional Easyclick receiver can not only receive radio signals, but also transmits back its status every time it changes. Actual ON/OFF switched states can then be visualised e.g. on the handheld transmitter D 450 FU-HS 128. The Easyclick receiver serves to switch lights and other electrical consumers. A range of functions and parameters can be selected:

two-key operation ON/OFF (standard function)

one-key operation ON/OFF (changeover)

button operation (pulse)

hotel card switch with definable follow-up time

stairwell light with selectable running time and shutdown warning

automatic OFF after selectable running time

fan function with delayed ON and with selectable follow-up time

save and retrieve 4 lighting scenes at the press of a key (one lighting scene per key)

window handle and window contact, visualisation also parallel to the switching outputs

movement detector and light sensor

A function can be defined individually for each of the max 32 programmed transmitters

Integrated repeater functions (1 level / 2 level) can be switched ON for each project, irrespectively of the set functions

Separate preassigned functions and parameters when e.g. window contacts, window handles, and movement detectors are being programmed

### Technical data:

Own consumption: < 0.5 W (bistable relay)

Transmit frequency: 868.3 MHz

Voltage supply: 100–240 Vac/ 50–60 Hz

Neutral conductor: required

Ambient temperature: -20 °C to +40 °C

Storage temperature: -40 °C to +85 °C

Plugin terminals: max 1 x 1.5 mm<sup>2</sup>

Housing height: 28 mm

Rating: IP 20

Mounting lugs: for screwing down in switch sockets

Approvals: CE; KEMA/KEUR

Load types 230 Vac (110 Vac)

Incandescent lamps 2500 W (1250 W)

HV halogen lamps 1200 W (600 W)

Motor load 600 VA (300 VA)

EVG load 3 pcs (3 pcs)

The quantity depends on the type and manufacturer. The device's data sheet must be observed!

Material No.	Article No.	EAN-code
00364376	D 451 FU-B EBI	4010105364378

---

### PEHA Elektro GmbH & Co.KG

a Honeywell Company

Daimlerstraße 4

58553 HALVER

DEUTSCHLAND

Tel.: 02353 9118 001

Fax: 02353 9118 311

mail: [peha@honeywell.de](mailto:peha@honeywell.de)

[www.peha.de](http://www.peha.de)

Änderungen vorbehalten. © Honeywell PEHA