

EnOcean Easyclickpro aerial module for DIN-rail system

Product Data Sheet



Other bus systems	Other
Model	Radio interface manufacturer specific
Mounting method	Surface mounted (plaster)
Degree of protection (IP)	IP20
With LED indication	No
Updateable	No
Operating voltage	24Volt
Visualization	Yes

EnOcean Easyclickpro aerial module for DIN-rail system

The bidirectional Easyclick aerial module receives all signals from Easyclick transmitters and repeaters inside its range. These are then rerouted via an RS485 interface to the Easyclick DIN-rail modules. The Easyclick modules are linked to each other with modular plug-in cables. Up to 128 modules can be connected to the RS485 bus. If required, also more than one aerial module can be connected to the Easyclick modular system. Technical data: Fitted with a white cover, the plastic housing is ready for surface mounting on a wall or ceiling.

Technical Data:

Connecting terminals for the RS485 bus

Rating: IP 20

Frequency: EnOcean 868.3 MHz

Own standby consumption: approx 0.4 W, operation approx 22 mA / 0.5 W

Housing measurements: dia approx 130 mm, H approx 29 mm

Material No.	Article No.	EAN-code
00377816	D 450 ANT	4010105377811

PEHA Elektro GmbH & Co.KGa Honeywell Company
Daimlerstraße 4
58553 HALVER
DEUTSCHLANDTel.: 02353 9118 001
Fax: 02353 9118 311
mail: peha@honeywell.de
www.peha.de

Änderungen vorbehalten. © Honeywell PEHA