

## EnOcean Easyclickpro module Switching, 4 channel, 10A, 2HP

## **Product Data Sheet**



Other bus systems	Other	
Mounting method	DRA (DIN-rail adapter)	
Width in number of modular spacings	2	
Local operation/hand operation	Yes	
With LED indication	Yes	
Max. switching power	2300Watt	
Suitable for C-load	Yes	
Max. number of switching contacts	4	
Different phases connectable	No	
Bus connection included	Yes	
Modular expandability	Yes	
2 channel 16 amps	no	
4 channel 10 amps	yes	
power supply included	no	



## EnOcean Easyclickpro module Switching, 4 channel, 10A, 2HP

The EnOcean Easyclick switching module receives its telegrams via the external Easyclick aerial module and uses its power sections to implement the configured functions and parameters. The Easyclick modules are linked to each other with modular plug-in cables. The Easyclick switching module is used to switch lights and other electrical consumers based on a range of functions and parameters configured at rotary switches. The four channels can be programmed independently of each other, and a function can be defined individually for each programmed transmitter.

Standard function: 2-key ON/OFF function. The functions selected can be e.g. 1-key function, time functions, fan control, window contact, lighting scene control, hotel card switch, time controlled power shutoff, temperature control, etc.

Technical data:

DRA device for mounting on 36 mm DIN rails (2 HP)

Own consumption: standby = approx 0.25 W operation = approx 70 mA / 1.7 W 4 relay outputs 10 A

Rotary switches for functions and parameters

Modular socket

LRN/CLR button

LED status display
incl 30 cm connecting cable

Rating: IP 20

Approvals: CE, KEMA/KEUR

Material No.	Article No.	EAN-code
00377856	D 454 FU-2REG	4010105377859

a Honeywell Company Daimlerstraße 4 58553 HALVER DEUTSCHLAND Tel.: 02353 9118 001 Fax: 02353 9118 311 mail: peha@honeywell.de

2

www.peha.de

Änderungen vorbehalten. © Honeywell PEHA