

Euro Single Rocker Self-powered Wireless Light Switch

315 MHz, E3T-S1Exx xx=WH, BK
868 MHz, E8T-S1Exx xx=WH, BK

Euro Double Rocker Self-powered Wireless Light Switch

315 MHz, E3T-S2Exx xx=WH, BK
868 MHz, E8T-S2Exx xx=WH, BK

ILLUMRA™ European style light switches are wireless and battery-free, delivering a no maintenance solution. Pressing the switch provides the energy needed to transmit a wireless signal that controls lights or other devices connected to ILLUMRA receivers.

Easy-To-Use

- Installs in minutes
- Requires no wiring
- Easy to configure
- Communicates with ILLUMRA receivers

Reliable Range

- 50-150 foot operating range
- Unique ID of each switch activates only the intended receiver(s)

Save Time and Money

Avoid costly and time-consuming installation of hard-wired switches by choosing ILLUMRA wireless switches and receivers. Installing a switch doesn't have to mean tearing open a wall anymore.

Save Energy

Save energy and money by creating Manual ON / Auto OFF controls using ILLUMRA switches and occupancy sensors or by programming all lights to respond to a single master switch. ILLUMRA makes it easy to keep lights and systems off when not in use!



Simple Wireless Control

- Mount switches anywhere
- Create 3-way and 4-way switches
- Control lights, motors, or other electrical loads
- Reconfigure or relocate as needed
- Unique (theft) tamper-resistant design

Control The Way You Want It

- Use with any line-voltage or low-voltage ILLUMRA receivers
- Control an unlimited number of ILLUMRA receivers within range
- Experience wireless dimming or ON/OFF control
- Maintenance-free operation for 20+ years

| | E3T-S1Exx, E8T-S1Exx | E3T-S2Exx, E8T-S2Exx |
|---------------------|--|-----------------------|
| Range | 50-150 feet (typical) | |
| Frequency | 315 MHz or 868 MHz | |
| Power Supply | Self-generated when switch is pressed | |
| Buttons | 2 Buttons (1 rocker) | 4 Buttons (2 rockers) |
| Output Channels | Only limited by number of receivers in range | |
| Dimensions | 3.16 (W) x 3.16 (H) x 0.40 (D) inches | |
| Radio Certification | FCC (United States): SZV-PTM200C, SZV-PTM200 I.C. (Canada): 5713A-PTM200C, 5713A-PTM200 | |
| Addressing | Factory set unique ID (1 of 4 billion) | |

Dimensions

