

## EnOcean Easyclick gateway for Centraline AX/NX controller

Product Data Sheet



Other bus systems	Other
Model	Radio interface manufacturer specific
Mounting method	Surface mounted (plaster)
Degree of protection (IP)	IP20
With LED indication	No
Updateable	No
Operating voltage	24Volt
Visualization	Yes
IR interface	No

## EnOcean Easyclick gateway for Centraline AX/NX controller

The aerial module is part of the PEHA Easyclick (EC) system. The aerial module was developed as a gateway between the PEHA Easyclick EnOcean products and the Centraline HAWK controller. The communication protocol between HAWK controller and the aerial module gateway is defined in a special software driver what is available for the Arena AX software. The signals are transmitted over the European harmonized frequency 868.3 MHz. The radio telegrams are forwarded through the RS485 bus to the HAWK. Similarly, any RS485 Message from the Hawk shall be broadcasted on the EnOcean network.

**Technical Data:**

Connecting terminals for the RS485 bus

Rating: IP 20

Frequency: EnOcean 868.3 MHz

Own standby consumption: approx 0.4 W, operation approx 22 mA / 0.5 W

Housing measurements: dia approx 130 mm, H approx 29 mm

Material No.	Article No.	EAN-code
00377806	D 450 ANT AX	4010105377804

---

**PEHA Elektro GmbH & Co.KG**

a Honeywell Company

Daimlerstraße 4

58553 HALVER

DEUTSCHLAND

Tel.: 02353 9118 001

Fax: 02353 9118 311

mail: [peha@honeywell.de](mailto:peha@honeywell.de)

[www.peha.de](http://www.peha.de)

Änderungen vorbehalten. © Honeywell PEHA