



LD-GW01/A

EnOcean to TCP/IP Gateway

The EnOcean to TCP/IP Gateway creates a powerful connection between devices on EnOcean protocol or TCP/IP Network. This gateway can learn numerous EnOcean devices, such as wireless switch, occupancy sensors etc.

Any device with EnOcean protocol can easily be connected with this LD-GW01 and controlled and managed remotely through a mobile APP.



GENERAL DATA

Operating temperature	-5°C to +40°C
Interface	1 Micro USB, 1 Ethernet, 1 power
Display	4 LED
Load number	Maximum 50 within effective distance

MECHANICAL DATA

Dimensions	119x74x22mm
Material	Aluminum, black
Protection	IP54

ELECTRICAL DATA

Power supply	5V DC, 2A
Power dissipation	5 W typ.

WIRELESS DATA

Antenna	External
Radio technology	EnOcean,868MHz, 4G, Wi-Fi/2.4G/802.11b/g/n, WEP (40/128bit), WPA, WPA2
Modulation technology	ASK
Transmission range	300m free field, typ. 30m within buildings



Room 301 Huashen Building,
Ruanjian Avenue,
Nanjing, Jiangsu Province
China

Tel: +86 025 5260 9811
Fax: +86 025 5260 9811
cuijj@win-shine.com

